

الالكترونيك بالايب

رقم	مدل	مميزات فني	تصوير	قيمت مصرف کننده (ريال)
IP Camera - IR				
1	SV-IPM8602-BV/WZ 	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8 -12mm Motorized Varifocal Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.05 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions		Hyperlink Call
2	NEW SV-IPNM8602-BZ/W	1/2.8" SONY CMOS Sensor 8MP(20FPS)/2.8 -12mm Motorized Varifocal Lens/3Stream/H.265+/H.264+ True WDR 120dB /50m IR/0.02 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/1CH audio input/SD Card Max 256GB /ONVIF/IP67 Metal SMART Functions		Hyperlink Call
3	SV-IPNH6201-BF/WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	  	Hyperlink Call
4	NEW SV-IPNH6503-DF/WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/1CH alarm input; 1CH alarm output/SD Card Max 256GB/ONVIF/IP67 & IK10 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	  	Hyperlink Call
5	SV-IPNH6301-DF/WSMFD	1/2.5" CMOS Sensor 6MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /Starlight/30m IR/0.008 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR, ANR, cloud upgrade POE/12VDC/1-1CH audio input-output and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata - Heat map-Support SMD (human / Motor Vehicle)	  	Hyperlink Call
6	SV-IPH4201-BF/W-MFD	1/3" CMOS Sensor 4MP(25FPS)/3.6 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /HFR(MAX 60fps in 1080p)/30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR POE/12VDC/1CH Audio Input/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata		Hyperlink Call

7	SV-IPH4301-DF/W-MFD	1/3" CMOS Sensor 4MP(25FPS)/2.8 mm fixed Lens/3Streams/H265+/H264+ True WDR 120dB /HFR(MAX 60fps in 1080p)/30m IR/0.005 Lux/ICR auto switch, true day / night ROI coding, AWB, 3D DNR, HLC, BLC, Defog, Smart IR POE/12VDC/1CH audio input and 1CH built-in MIC/SD Card Max 256GB/ONVIF/IP67 Metal SMART Functions- People/vehicle counting- Face detection and face capture- Video Metadata	  	Hyperlink Call
8	SV-IPH21602-BZ/WSLR 7-22mm	2MP ANPR Network Camera; Speed: up to 70 KM/H 1/2.8" SONY CMOS Sensor 2MP(25FPS) / 1080P 60fps in HFR mode 7-22mm Motorized Varifocal Lens 3Streams/Smart coding H.265S/H.264S/H265+/H264+ True WDR 120dB /Starlight /100m IR /0.005 Lux, ICR auto switch, true day/night ROI coding, AWB, 3D DNR, HLC, BLC, defog, Smart IR POE/12VDC/ 1CH audio input; 1CH audio output/ 1CH alarm input; 1CH alarm output /SD Card Max 256GB/ CVBS output/RS485/Wiegand/ONVIF/IP67 Metal SMART Functions- Supports license plate recognition LPR Distance: 4 ~ 17m	 	Hyperlink Call
9	SV-IPH4901/PZ37X/SFR	1/1.8" progressive scan CMOS Sensor 4MP(25FPS)/ 5.6 ~ 208 mm Motorized Lens/37x Optical Zoom/500m VCSEL IR/H.265,H.264/DWDR/Starlight 1 Ch input, 1 Ch output Audio/7 Ch input ,2 Ch output Alarm/SD Card Max 256GB/CVBS Analog Output/RS485/ IP67, IK10 Metal/Outdoor/ AC24V 5A, DC24V,PoE++ SMART Functions/ Auto Tracking/ Supports face detection and comparison/ Target counting	  8inch 	Hyperlink Call
10	SV-IPM4706/PZ25X/WSFR	1/2.7" progressive scan CMOS, BSI, NIR+/ 4MP(25FPS)/ 4.8 ~ 120 mm Motorized Lens/25x Optical Zoom/160m SMART IR/H.265+,H.264+/True WDR 120dB/Starlight 1 Ch input, 1 Ch output Audio/1CH Alarm input; 1CH Alarm output/SD Card Max 256GB/IP66, IK10 Metal /DC12V 3A, ,PoE+ SMART Functions/ Auto Tracking/ Supports face detection and recognition/ Target counting	  4inch 	Hyperlink Call
11	SV-IPHP842-SFR	8MP 180° Panoramic Network Camera 1/2.8" SONY(4pcs*2MP) progressive scan CMOS Sensor / 8MP(4096 × 1800) (25FPS) 3.2mm fixed Lens x 4 /3Streams/H.265+/H.264+ DWDR/ Starlight/ 20m IR/ 0.008 lux/ 12V DC/ PoE/ ONVIF 1/1 CH Audio In/Output , 1/1 CH Alarm In/Output, SD Card Max 256GB, RS485 3D DNR, HLC, BLC, defog, EIS, IP67, IK10 SMART Functions / Supports face detection and comparison	  Panoramic Image 	Hyperlink Call
12	SV-IPFPS27M	Face Panel & Access Control Terminal Standalone/7 inch LCD screen/Face Liveness Detection 1/2.8" progressive scan CMOS Sensor/ 2MP(25FPS) 4.3 mm x 2 lens/3Streams/H265+/H264+/ WDR(72dB), 3D DNR, HLC, BLC, defog, DC12V/1A Face Recognition Distance: 1.5m Face Picture Database: 10,000 White Light Distance: 1m soft light IR Light Distance: 2m 1 Built-in MIC/Built-in Speaker - 1/1 CH Alarm In/Output 1CH RJ45-1CH Wiegand-1CH Lock-1CH Door contact input-Exit Buttonx1-Tamper Buttonx1-Built-in card reader door opening modes (Only card, Only face recognition, card and face recognition, card Or face recognition) Card Type: Mifare Card/Desfire Card/FM1208 Card/Gicard SMART Functions /Supports face detection and comparison	  	Hyperlink Call

13	SV-IP2SPH-WFD	2MP Pinhole Camera 1/2.8" SONY Progressive Scan CMOS 2MP(25FPS)/2.8 mm fixed Lens/3Stream/H.265+/H.264+ True WDR 120dB (HD camera) /0.05 Lux ROI coding, 3D DNR, HLC, BLC, defog POE/12VDC, 1/1 CH Audio In/Output, 8/4 CH Alarm In/Output, 1CH BNC video input connector, SD Card Max 256GB /ONVIF/ Support UTC control SMART Functions/Perimeter protection/Supports Face detection and face capture/ target counting	HD camera + Converter  WDR	Hyperlink Call
Light Explorer IP Camera - Color View				
14	SV-IPCV24602-BF/W	1/3" CMOS Sensor 4MP(25FPS)/ 6mm fixed Lens/3Streams/H.265/ H.264/ True WDR 120dB/30~ 40m white light view distance/0.003 lux ROI coding, AWB, 3D DNR, HLC, BLC POE/12VDC/1CH audio input; 1CH built-in MIC /SD Card Max 256GB/ ONVIF/IP67(Metal&Plastic) SMART Functions	Full-Clear WDR  Microphone icon	Hyperlink Call
NVR				
15	NEW SV-16N2801/1H5S-AI	8CH input & Record 16MP(25FPS)/ H.265S/H.265+/H.264/ Bandwidth(Input 160Mbps/Output 160Mbps) 8CH IPC Audio input/8Ch local Alarm input - 4Ch Output/1HDD*10TB 4K HDMI-VGA/2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M *2 AI Function- Supports face detection and comparison (8CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/ Supports fisheye camera access قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	Deep Learning Algorithm VCA Face Recognition  License plate recognition Metadata Fisheye	Hyperlink Call
16	NEW SV-16N21601/2H5S-AI	16CH input & Record 16MP(25FPS)/ H.265S/H.265+/H.264/ Bandwidth(Input 192Mbps/Output 192Mbps) 16CH IPC Audio input/8Ch local Alarm input - 4Ch Output/2HDD*10TB 4K HDMI-VGA/2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M *2 AI Function- Supports face detection and comparison (16CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/ Supports fisheye camera access قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	Deep Learning Algorithm VCA Face Recognition  License plate recognition Metadata Fisheye	Hyperlink Call
17	SV-12N3201/2H5S-AI 	32CH input & Record 12MP(25FPS)/ H.265S/H.265+/H.265/ Bandwidth(Input 192Mbps/Output 192Mbps) 32CH IPC Audio input/8Ch local Alarm input - 4Ch Output/2HDD*10TB HDMI*2(4K & 1080P)-VGA/2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M * 2 AI Function-Supports face detection and comparison (32CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	Deep Learning Algorithm VCA Face Recognition  License plate recognition Metadata	Hyperlink Call

18	SV-12N23201/4H5S-AI	32CH input & Record 12MP(20fps), 9MP or lower(25fps) H.265S/H.265+/H265/ Bandwidth(Input 320Mbps/Output 256Mbps) 32CH IPC Audio input/16Ch local Alarm input - 4Ch Output/4HDD*10TB/eSATA*1/ HDMI*2(4K & 1080P)-VGA/2 RCA AUDIO IN & OUT/RS485*2/ USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M * 2 AI Function-Supports face detection and comparison (32CH - AI by IPC / 2CH - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	    	Hyperlink 
19	SV-12N3201/8H5S-AI	32CH input & Record 12MP@20fps; 8MP or lower@25fps/ H.265S/H.265+/H265/ Bandwidth(Input 320Mbps/Output 320Mbps) 32CH IPC Audio input/16Ch local Alarm input - 4Ch Output/8HDD*10TB/eSATA*1 HDMI*2(4K & 1080P)-VGA/2 RCA AUDIO IN & OUT/RS485*2/Supports RAID0, RAID1, RAID5, RAID6, RAID10 USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M * 2 AI Function- Supports face detection and comparison (32CH - AI by IPC / 2CH (2MP) - AI by Device) / License plate recognition/ Video Metadata/Support fisheye (Web Client and mobile APP) قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	     	Hyperlink 
20	SV-16N6401/8H5S-8K-AI	64CH input & Record 16MP@25fps H.265S/H.265+/H265/ Bandwidth(Input 640Mbps/Output 640Mbps) 64CH IPC Audio input/ 8HDD*10TB/eSATA*2 HDMI*4(8k & 4K & 1080P)-VGA/2 RCA AUDIO IN & OUT/16Ch local Alarm input - 4Ch Output/RS485*2/Supports RAID0, RAID1, RAID5, RAID6, RAID10 USB2.0*2 & USB3.0*1/P2P/ONVIF/DHCP/DDNS/ RJ45 10-100-1000M * 2 AI Function- Supports face detection and comparison (64CH - AI by IPC / 4CH - AI by Device) / License plate recognition/ Video Metadata/ Fisheye قابلیت پشتیبانی از تقویم شمسی و منوی فارسی	     	Hyperlink 

وبسایت: Scanviewcctv.com

تلگرام: [scanviewcctv](https://t.me/scanviewcctv)

تلفن: 09143073257