

Tiandy

2MP Bullet



AK



AK



AK



Spark



Spark



Part number	TC-C321N Spec:I3/E/Y/2.8mm	TC-C321N Spec:AK/I3W/E/Y/2.8mm/V2.0	TC-C321N 1ANB-28	TC-C32QN Spec:I3/E/Y/2.8mm/V5.0	TC-C32QV 2FNA-28
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color:0.0002Lux@(F1.0,AGC ON)
WDR	DWDR	DWDR	DWDR	DWDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m + Warmlight	IR range up to 30m	Warmlight
Body Material	Metal+plastic housing	Plastic housing	Plastic housing	Metal+plastic housing	Metal+plastic housing
VCA	N/A	N/A	N/A	N/A	Smart Alarm
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	PoE:IEEE 802.3af,Max. 6W	PoE:IEEE 802.3af,Max. 3W	PoE:IEEE 802.3af,Max. 2.5W	PoE:IEEE 802.3af,Max. 6W	DC12V±25%,Max. 4.5W PoE:IEEE 802.3af,Max. 6W
Click Or Scan For More					
Price	72,000,000 ریال	78,500,000 ریال	78,500,000 ریال	74,500,000 ریال	158,300,000 ریال



پرسیا سیستم



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

2MP Bullet



Spark



Super Lite



Super Lite



Lite



Lite



Part number	TC-C32RN Spec:I5/E/Y/QX/2.8mm/V4.2	TC-C32QN Spec:I5W/E/Y/2.8mm/V4.2	TC-C32GN Spec:I5/E/Y/C/2.8mm/V4.2	TC-C32WP Spec:I5W/E/Y/2.8mm/V4.2	TC-C32WP Spec:I5W/E/Y/M/2.8mm/V4.2
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	DWDR	DWDR	DWDR	WDR	WDR
Lens	Fixed (2.8 mm)	Fixed (2.8 mm)	Fixed (2.8 mm)	Fixed (2.8 mm)	Fixed (2.8 mm)
Night Vision	IR range up to 50m	IR range up to 50m + Warmlight	IR range up to 50m	IR range up to 50m + Warmlight	IR range up to 50m + Warmlight
Body Material	Plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal housing
VCA	N/A	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	DC12V±25%,Max. 7.5W PoE:IEEE 802.3af,Max. 8.5W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 7W	PoE:IEEE 802.3af,Max. 7W	DC12V±25%,MAX 6W PoE:IEEE 802.3af,MAX 7W	DC12V±25%,MAX 6W PoE:IEEE 802.3af,MAX 7W
Click Or Scan For More					
Price	ريال 143,000,000	ريال 82,500,000	Discontinue	ريال 109,500,000	Discontinue



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

2MP Bullet



Part number	TC-C32US Spec:I8/A/E/Y/M/C/H/2.7-13.5mm/V4.0	TC-C32UP Spec:W/E/Y/M/H/4mm/V4.0	TC-C32WS Spec:I5/E/Y/M/2.8mm/V4.0	TC-C32TS Spec:I8/A/E/Y/M/H/2.7-13.5mm/V4.0	TC-C32TS Spec:I8/A/E/Y/M/H/2.7-13.5mm/V4.1
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@60fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color: 0.0004Lux@ (F1.0, AGC ON) B/W: 0Lux with LED on	Color: 0.001Lux@ (F1.6, AGC ON) B/W: 0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Motorized (2.7-13.5mm)	Fixed (4mm)	Fixed (2.8mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)
Night Vision	IR range up to 80m	Warmlight	IR range up to 50m	IR range up to 80m	IR range up to 80m
Body Material	Metal housing	Metal housing	Metal Housing	Metal Housing	Metal Housing
VCA	Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 11 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	DC12V±25%,Max. 8W PoE:IEEE 802.3af,Max. 9W	DC12V±25% PoE:IEEE 802.3af	DC12V±25% PoE:IEEE 802.3af	DC12V±25%,Max. 9W PoE:IEEE 802.3af,Max. 10W	DC12V±25%,Max. 9W PoE:IEEE 802.3af,Max. 10W
Click Or Scan For More					
Price	ريال 270,000,000	ريال 220,000,000	Call	ريال 245,000,000	ريال 245,000,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

2MP Dome



AK



AK



AK



Spark



Spark



Part number	TC-C320N Spec:I3/E/Y/2.8mm	TC-C320N Spec:AK/I3W/E/Y/2.8mm/V2.0	TC-C320N 1ANB-28	TC-C32XN Spec:I3/E/Y/2.8mm/V5.0	TC-C32XV 2FNA-28
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color:0.0002Lux@(F1.0,AGC ON)
WDR	DWDR	DWDR	DWDR	DWDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m + Warmlight	IR range up to 30m	Warmlight
Body Material	Metal+plastic housing	Plastic housing	Plastic housing	Metal+Plastic Housing	Metal+Plastic Housing
VCA	N/A	N/A	N/A	N/A	Smart Alarm
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP66	IP66	IP66	IP66	IP66
Power Supply	PoE:IEEE 802.3af,Max. 6W	PoE:IEEE 802.3af,Max. 2.5W	PoE:IEEE 802.3af,Max. 2.5W	PoE:IEEE 802.3af,MAX 6W	DC12V±25%,Max. 4.5W PoE:IEEE 802.3af,Max. 6W
Click Or Scan For More					
Price	72,000,000 ریال	78,500,000 ریال	78,500,000 ریال	74,500,000 ریال	158,300,000 ریال



پرسیا سیستم



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

2MP Dome



Super Lite



Super Lite



Lite



Lite



Lite



Part number	TC-C32XN Spec:I3W/E/Y/2.8mm/V4.2	TC-C32HN Spec:I3/E/Y/C/2.8mm/V4.2	TC-C32XP Spec:I3/E/Y/M/Z/2.8mm/V4.0	TC-C32XP Spec:I3W/E/Y/2.8mm/V4.2	TC-C32XP Spec:I3W/E/Y/M/2.8mm/V4.2
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color: 0.0008Lux@ (F1.6, AGC ON) B/W: 0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	DWDR	DWDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m + Warmlight	IR range up to 30m	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m + Warmlight
Body Material	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal housing
VCA	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP66	IP66	IP66	IP66	IP66
Power Supply	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 7W	PoE:IEEE 802.3af,Max. 7W	DC12V±25% PoE:IEEE 802.3af	DC12V±25%,MAX 6W PoE:IEEE 802.3af,MAX 7W	DC12V±25%,MAX 6W PoE:IEEE 802.3af,MAX 7W
Click Or Scan For More					
Price	94,500,000 ریال	Discontinue	101,400,000 ریال	Discontinue	109,500,000 ریال



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

2MP Dome



Super Lite



Pro



Lite



Pro



Pro



Part number	TC-C32KN Spec:I3/E/Y/C/2.8mm/V4.3	TC-C32KS Spec:I3/E/Y/C/H/2.8mm/V4.0	TC-C32MS Spec:I3/A/E/Y/M/C/H/2.7-13.5mm/V4.0	TC-C32MS Spec:I5/A/E/Y/M/H/2.7-13.5mm/V4.0	TC-C32MP Spec:I5/A/E/Y/M/H/2.7-13.5mm/V4.0
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color: 0.002Lux@ (F1.6, AGC ON) B/W: 0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color: 0.0004Lux@ (F1.2, AGC ON) B/W: 0Lux with IR
WDR	DWDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)
Night Vision	IR range up to 30m	IR range up to 30m	IR range up to 30m	IR range up to 50m	IR range up to 50m
Body Material	Plastic housing	Metal-plastic housing	Metal+plastic housing	Metal housing	Metal housing
VCA	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 10 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 11 more ...
Audio I/O & Alarm I/O	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output
Protection	IP66	IP66, IK10	IP66, IK10	IP66, IK10	IP67, IK10
Power Supply	DC12V±25%,Max. 4.5 PoE:IEEE 802.3af,Max. 5W	DC 12V±25% PoE:IEEE 802.3af	DC12V±25%,Max. 7W PoE:IEEE 802.3af,Max. 8W	DC12V PoE:IEEE 802.3af	DC12V±25% PoE:IEEE 802.3af
Click Or Scan For More					
Price	ريال 130,000,000	Call	ريال 240,000,000	ريال 245,000,000	ريال 260,000,000



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

4MP Bullet



Spark



Spark



Super Lite



Super Lite



Super Lite



Part number	TC-C34QN Spec:I3/E/Y/2.8mm/V5.0	TC-C34QN 2ENA-28	TC-C34QN Spec:I5W/E/Y/2.8mm/V4.2	TC-C34GS Spec:I5/E/Y/C/SD/2.8mm/V4.2	TC-C34UN Spec:I8/A/E/Y/2.8-12mm/V4.2
Max. Resolution	Up to 4MP,2560×1440@20fps	Up to 4MP,2560×1440@30fps	Up to 4MP,2688×1520@25fps	Up to 4MP,2688×1520@25fps	Up to 4MP,2688×1520@25fps
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.001Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	DWDR	DWDR	WDR	DWDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Motorized (2.8-12mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 50m + Warmlight	IR range up to 50m	IR range up to 80m
Body Material	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing
VCA	N/A	N/A	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	PoE:IEEE 802.3af,Max. 6W	PoE:IEEE 802.3af,Max. 4W	DC12V±25%,Max. 6.5 PoE:IEEE 802.3af,Max. 7W	PoE:IEEE 802.3af,Max. 7W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 7W
Click Or Scan For More					
Price	ريال 107,500,000	ريال 148,500,000	ريال 151,000,000	ريال 140,000,000	Discontinue



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

4MP Bullet



Lite

TC-C34UP
Spec:W/E/Y/M/4mm/V4.0

Part number

Max. Resolution

Up to 4MP,2595×1520@25fps

Min. Illumination

Color:0.0004Lux@(F1.0,AGC ON)

WDR

WDR

Lens

Fixed (4mm)

Night Vision

Warmlight

Body Material

Metal housing

VCA

Tripwire; Perimeter

Audio I/O & Alarm I/O

N/A

Protection

IP67

Power Supply

DC12V±25%,MAX 8
PoE:IEEE 802.3af,MAX 9W

Click Or Scan For More



Price

Call



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

4MP Dome



Spark



Spark



Super Lite



Super Lite



Lite



Part number	TC-C34XN Spec:I3/E/Y/2.8mm/V5.0	TC-C34XN 2ENA-28	TC-C34XN Spec:I3W/E/Y/2.8mm/V4.2	TC-C34HS Spec:I3/E/Y/C/SD/2.8mm/V4.0	TC-C34XS Spec:I3W/E/Y/2.8mm/V4.2
Max. Resolution	Up to 4MP,2560×1440@20fps	Up to 4MP,2560×1440@30fps	Up to 4MP,2688×1520@25fps	Up to 4MP,2688×1520@25fps	Up to 4MP,2592×1520@25fps
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.001Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	DWDR	DWDR	WDR	DWDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m + Warmlight	IR range up to 30m	IR range up to 30m + Warmlight
Body Material	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing
VCA	N/A	N/A	Tripwire; Perimeter	Tripwire; Perimeter	Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	IP66	IP66	IP66	IP66	IP66
Power Supply	PoE:IEEE 802.3af,Max. 6W	PoE:IEEE 802.3af,Max. 4W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 7W	PoE:IEEE 802.3af,MAX 7W	DC12V±25%,MAX 6W PoE:IEEE 802.3af,MAX 7W
Click Or Scan For More					
Price	ريال 107,500,000	ريال 148,500,000	ريال 148,000,000	ريال 122,000,000	Discontinue



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

5&6MP Bullet



Part number	TC-C35WS 3ERA-28	TC-C35WS 3LRA-28	TC-C35UV Spec:W/E/Y/M/S/4mm	TC-C35US 3LHA-27135	TC-C35US Spec:I8/A/E/Y/M/C/H/2.7-13.5mm/V4.0
Max. Resolution	Up to 5MP,3072×1728@20fps	Up to 5MP,3072×1728@20fps	Up to 5MP,3072×1728@30fps	Up to 5MP,3072×1728@20fps	Up to 5MP,2592×1944@20fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.0001Lux@(F1.0,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (4mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)
Night Vision	IR range up to 50m + Warmlight	IR range up to 50m + Warmlight	Warmlight	IR range up to 80m + Warmlight	IR range up to 80m
Body Material	Metal+plastic housing	Metal housing	Metal housing	Metal housing	Metal housing
VCA	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	DC12V±25%,Max. 7W PoE:IEEE 802.3af,Max. 7.5W	DC12V±25%,Max. 6W PoE:IEEE 802.3af,Max. 7W	DC12V±25%,Max. 8W PoE:IEEE 802.3af,Max. 9W	DC12V±25%,Max. 8W PoE:IEEE 802.3af,Max. 9W	DC12V±25%,Max. 8W PoE:IEEE 802.3af,Max. 9W
Click Or Scan For More					
Price	220,000,000 ریال	Call	Call	320,000,000 ریال	Discontinue



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگرد



Tiandy

5&6MP Bullet



Part number	TC-C35US Spec:LK/I5W/E/Y/M/S/2.8mm/V5.0	TC-C35WQ Spec:I5W/E/Y/2.8mm/V4.2	TC-C35US Spec:I8/A/E/Y/M/S/H/2.7-13.5mm/V4.0	TC-C35TS Spec:I8/A/E/Y/M/H/2.7-13.5mm/V4.1	TC-C35LP Spec:I8W/A/E/Y/M/H/2.7-13.5mm/V4.0
Max. Resolution	Up to 5MP,2880×1620@30fps	Up to 5MP,2880×1620@30fps	Up to 5MP,2880×1620@30fps	Up to 5MP,2880×1620@30fps	Up to 5MP,3072×1728@30fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.0004Lux@(F1.3,AGC ON) B/W:0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)
Night Vision	IR range up to 50m + Warmlight	IR range up to 50m + Warmlight	IR range up to 80m	IR range up to 80m	IR range up to 80m + Warmlight
Body Material	Metal housing	Metal housing	Metal housing	Metal housing	Metal+plastic housing
VCA	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...
Audio I/O & Alarm I/O	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	DC12V±25%,Max. 8W PoE:IEEE 802.3af,Max. 9W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 8W	DC12V±25%,Max. 9.5W PoE:IEEE 802.3af,Max. 10.5W	DC12V±25%,Max. 9.5W PoE:IEEE 802.3af,Max. 10.5W	DC12V±25%,Max. 14W PoE:IEEE 802.3at,Max. 15.5W
Click Or Scan For More					
Price	210,000,000 ریال	346,000,000 ریال	Call	Call	Call



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

5&6MP Bullet



Pro



Spark



Part number	TC-C35LQ Spec:15W/E/Y/T/4mm/V4.2	TC-C36QN 2ENA-28		
Max. Resolution	Termal: 1MP,1280×720@25fps Optical: 5MP,2880×1620@30fps	Up to 6MP,3200×1800@30fps		
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.001Lux@(F1.6,AGC ON) B/W:0Lux with IR		
WDR	WDR	WDR		
Lens	Termal: Fixed (3mm) Optical: Fixed (4mm)	Fixed (2.8mm)		
Night Vision	IR range up to 50m + Warmlight	IR range up to 30m + Warmlight		
Body Material	Metal+plastic housing	Metal+plastic housing		
VCA	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; Video Abnormal; Audio Abnormal	N/A		
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	N/A		
Protection	IP67	IP67		
Power Supply	DC12V±25%,Max. 9W PoE:IEEE 802.3af,Max. 10W	PoE:IEEE 802.3af,Max. 5W		
Click Or Scan For More				
Price	Call	207,700,000 ریال		



پرسیا سیستم



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

5&6MP Dome



Lite



Lite



Pro



Lite



Lite



Part number	TC-C35XS Spec:I3/E/Y/2.8mm/V4.0	TC-C35XS 3ERA-28	TC-C35XQ Spec:I3W/E/Y/2.8mm/V4.2	TC-C35KS Spec:I3/E/Y/2.8mm/V4.0	TC-C35KS 3ERA-28
Max. Resolution	Up to 5MP,2592×1944@20fps	Up to 5MP,3072×1728@30fps	Up to 5MP,2880×1620@30fps	Up to 5MP,2592×1944@20fps	Up to 5MP,3072×1728@20fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m + Warmlight	IR range up to 30m	IR range up to 30m + Warmlight
Body Material	Metal+plastic housing	Metal+plastic housing	Metal housing	Metal+plastic housing	Metal+plastic housing
VCA	Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter
Audio I/O & Alarm I/O	N/A	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	N/A	N/A
Protection	IP66	IP67	IP66	IP66; IK10	IP67; IK10
Power Supply	DC12V±25%,Max. 6W PoE:IEEE 802.3af,Max. 7W	DC12V±25%,Max. 4.5W PoE:IEEE 802.3af,Max. 5W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 8W	DC12V±25%,Max. 6W PoE:IEEE 802.3af,Max. 7W	DC12V±25%,Max. 7 PoE:IEEE 802.3af,Max. 7.5W
Click Or Scan For More					
Price	Discontinue	ريال 220,000,000	ريال 340,000,000	Discontinue	ريال 230,000,000



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

5&6MP Dome



Lite



Lite



Pro



Pro



Pro



Part number	TC-C35MS Spec:I3/A/E/Y/M/2.8-12mm	TC-C35MS Spec:I3/A/E/Y/M/C/H/2.7-13.5mm/V4.0	TC-C35KS Spec:I3/E/Y/M/H/2.8mm/V4.0	TC-C35MS Spec:I3/A/E/Y/M/S/H/2.7-13.5mm/V4.0	TC-C35MS Spec:I5/A/E/Y/M/H/2.7-13.5mm/V4.0
Max. Resolution	Up to 5MP,2592×1944@20fps	Up to 5MP,2592×1944@20fps	Up to 5MP,2592×1944@30fps	Up to 5MP,2880×1620@30fps	Up to 5MP,2880×1620@30fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color: 0.002Lux@ (F1.6, AGC ON) B/W: 0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Motorized (2.8-12mm)	Motorized (2.7-13.5mm)	Fixed (2.8mm)	Motorized (2.7-13.5mm)	Motorized (2.7-13.5mm)
Night Vision	IR range up to 30m	IR range up to 30m	IR range up to 30m	IR range up to 30m	IR range up to 50m
Body Material	Metal housing	Metal-plastic housing	Metal housing	Metal housing	Metal housing
VCA	Tripwire; Perimeter	Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...
Audio I/O & Alarm I/O	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output
Protection	IP66, IK10	IP66, IK10	IP67, IK10	IP66, IK10	IP66, IK10
Power Supply	DC12V±25%,MAX 7W PoE:IEEE 802.3af,MAX 8W	DC12V±25%,Max. 7W PoE:IEEE 802.3af,Max. 8W	DC12V±25% PoE:IEEE 802.3af	DC12V±25%,MAX 8W PoE:IEEE 802.3af,MAX 9W	DC12V±25%,MAX 8W PoE:IEEE 802.3af,MAX 9W
Click Or Scan For More					
Price	250,000,000 ریال	Discontinue	Call	Call	Call



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

5&6MP Dome



Part number	TC-C35MP Spec:I5/A/E/Y/M/H/2.7-13.5mm/V4.0	TC-C35PS Spec:I3/E/Y/M/H/2.8mm/V4.2	TC-C36XN 2ENA-28		
Max. Resolution	Up to 5MP,2592×1944@30fps	Up to 5MP,2880×1620@30fps	Up to 6MP,3200×1800@30fps		
Min. Illumination	Color: 0.001Lux@ (F1.3, ACG ON) B/W: 0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.001Lux@(F1.6,AGC ON) B/W:0Lux with IR		
WDR	WDR	WDR	WDR		
Lens	Motorized (2.7-13.5mm)	Fixed (2.8mm)	Fixed (2.8mm)		
Night Vision	IR range up to 50m	IR range up to 30m	IR range up to 30m + Warmlight		
Body Material	Metal housing	Metal housing	Metal+plastic housing		
VCA	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	N/A		
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	N/A		
Protection	IP67, IK10	IP66, IK08	IP66		
Power Supply	DC12V±25% PoE:IEEE 802.3af	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 8W	PoE:IEEE 802.3af,Max. 5W		
Click Or Scan For More					
Price	Call	Call	207,700,000 ریال		



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

8MP Bullet



Part number	TC-C38WS 3LRA-28	TC-C38WS Spec:I5/E/Y/M/H/2.8mm/V4.0	TC-C38TS Spec:I8/A/E/Y/M/H/2.7-13.5mm	TC-C382V Spec:W/E/Y/S/H/2.8mm	TC-A38N5 Spec:0/A/10-47mm
Max. Resolution	Up to 8MP,3840×2160@20fps	Up to 8MP,3840×2160@30fps	Up to 8MP,3840×2160@20fps	Up to 8MP,4640×1728@25fps	Up to 8MP,3840×2160@30fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color: 0.003Lux@ (F1.6, AGC ON) B/W: 0Lux with IR	Color:0.0001Lux@(F1.0,AGC ON) B/W:0Lux with IR	Color: 0.01Lux@ (F1.35, AGC ON)
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Motorized (2.7-13.5mm)	Fixed (2.8mm)	Motorized (10-47mm)
Night Vision	IR range up to 50m + Warmlight	IR range up to 50m	IR range up to 80m	Warmlight	Warmlight
Body Material	Metal housing	Metal housing	Metal housing	Metal+plastic housing	Metal housing
VCA	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Human/Vehicle Classification; Tripwire; Perimeter; Video Abnormal; Audio Abnormal	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...
Audio I/O & Alarm I/O	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output
Protection	IP67	IP67	IP67	IP67	IP67
Power Supply	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 8W	DC12V±25%,Max. 6.5W PoE:IEEE 802.3af,Max. 8W	DC12V±25%,PoE	DC12V±25%,Max. 9W PoE:IEEE 802.3at,Max. 9.5W	AC24V±25%
Click Or Scan For More					
Price	322,500,000 ریال	Call	Call	Call	Call



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگرد



Tiandy

8MP Dome



Lite



Lite



Lite



Lite



Pro



Part number	TC-C38XS Spec:I3/E/Y/M/2.8mm/V4.0	TC-C38XS 3LRA-28	TC-C38KS Spec:I3/E/Y/2.8mm/V4.0	TC-C38KS 3ERA-28	TC-C38KS Spec:I3/E/Y/M/H/2.8mm/V4.0
Max. Resolution	Up to 8MP,3840×2160@20fps	Up to 8MP,3840×2160@20fps	Up to 8MP,3840×2160@20fps	Up to 8MP,3840×2160@20fps	Up to 8MP,3840×2160@20fps
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color: 0.003Lux@ (F1.6, AGC ON) B/W: 0Lux with IR
WDR	WDR	WDR	WDR	WDR	WDR
Lens	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)
Night Vision	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m	IR range up to 30m + Warmlight	IR range up to 30m
Body Material	Metal housing	Metal housing	Metal+plastic housing	Metal+plastic housing	Metal housing
VCA	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Perimeter	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output
Protection	IP66	IP67	IP66; IK10	IP67; IK10	IP67; IK10
Power Supply	DC12V±25%,Max. 7W PoE:IEEE 802.3af,Max. 8.5W	DC12V±25%,Max. 7W PoE:IEEE 802.3af,Max. 8.5W	DC12V±25%,Max. 6W PoE:IEEE 802.3af,Max. 7.5W	DC12V±25%,Max. 6W PoE:IEEE 802.3af,Max. 7.5W	DC12V±25%,PoE
Click Or Scan For More					
Price	Discontinue	322,500,000 ریال	Discontinue	338,500,000 ریال	Call



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

8MP Dome



Pro

TC-C38MS

Spec: I5/A/E/Y/M/H/2.7-13.5mm/V4.0

Part number

Max. Resolution

Up to 8MP, 3840×2160@30fps

Min. Illumination

Color: 0.002Lux@ (F1.6, AGC ON)
B/W: 0Lux with IR

WDR

WDR

Lens

Motorized (2.7-13.5mm)

Night Vision

IR range up to 50m

Body Material

Metal housing

VCA

Human/Vehicle Classification; Tripwire;
Double Tripwire; Perimeter;
[+ 12 more ...](#)

Audio I/O & Alarm I/O

Audio I/O: 1×input, 1×output
Alarm I/O: 2×input, 1×output

Protection

IP66; IK10

Power Supply

DC12V±25%, Max. 8W
PoE: IEEE 802.3af, Max. 9W

Click Or Scan For More



Price

Call



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

Wifi Series



Part number	TC-H332N Spec:I2W/WIFI/4mm/V4.1	TC-C32CN Spec:I3W/U/WIFI/2.8mm/V4.0	TC-C32KN Spec:I3/Y/WIFI/2.8mm	TC-C34QN Spec:I5W/WIFI/Eu/2.8mm/V4.0	TC-H333K Spec:AK/I5W/WIFI/Eu/4mm
Max. Resolution	Up to 3MP,2304x1296@20fps	Up to 2MP,1920x1080@25fps	Up to 2MP,1920x1080@30fps	Up to 4MP,2560x1440@20fps	Up to 3MP,2304x1296@20fps
Min. Illumination	Color:0.02Lux@ (F2.0, AGC ON) B/W:0Lux with IR	Color:0.02Lux@ (F2.0,AGC ON) B/W:0Lux with IR	Color: 0.02Lux@ (F2.0, AGC ON) B/W: 0Lux with IR	Color:0.02Lux@ (F2.0,AGC ON) B/W:0Lux with IR	Color:0.001lux@ (F1.6,AGC ON) B/W:0Lux with IR
WDR	DWDR	DWDR	DWDR	DWDR	DWDR
Lens	Fixed (4mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (2.8mm)	Fixed (4mm)
Night Vision	IR range up to 20m + Warmlight	IR range up to 30m + Warmlight	IR range up to 30m	IR range up to 50m + Warmlight	IR range up to 30m + Warmlight
Body Material	Plastic housing	Plastic housing	Metal+plastic housing	Metal+plastic housing	Plastic housing
VCA	N/A	Smart Alarm	N/A	Smart Alarm	Smart Alarm
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
Protection	N/A	IP65	IP66, IK10	IP67	IP66
Power Supply	DC12V±25%	DC5V±25%	DC12V±25%	DC12V±25%,Max. 7.5W	DC12V±25%,Max. 12W
Click Or Scan For More					
Price	Call	Call	140,000,000 ریال	Call	157,000,000 ریال



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

Wifi Series



Wifi



Wifi



Wifi



Part number	TC-H333N Spec:15W/C/WIFI/4mm/V4.2	TC-H363N Spec:15W/WIFI/Eu/4mm/V4.0	TC-H363U Spec:W/4G/U/SE/4mm/V4.1		
Max. Resolution	Up to 3MP,2304×1296@20fps	Panorama: 3MP,2304×1296@15fps Detail: 3MP,2304×1296@15fps	Panorama: 3MP,2304×1296@15fps Detail: 3MP,2304×1296@15fps		
Min. Illumination	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.02Lux@(F1.6,AGC ON) B/W:0Lux with IR	Color:0.002Lux@(F1.6,AGC ON) B/W:0Lux with IR		
WDR	DWDR	DWDR	DWDR		
Lens	Fixed (4mm)	Fixed (4mm)	Fixed (4mm)		
Night Vision	IR range up to 50m + Warmlight	IR range up to 50m + Warmlight	Warmlight		
Body Material	Plastic housing	Plastic housing	Plastic housing		
VCA	Smart Alarm	Smart Alarm	N/A		
Audio I/O & Alarm I/O	N/A	N/A	N/A		
Protection	IP66	IP66	IP65		
Power Supply	DC12V±25%,Max. 12W	DC12V±25%,Max. 13W	DC5V±25%		
Click Or Scan For More					
Price	Call	Call	630,000,000 ریال		



پرسیا سیستم



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

Fisheye



Lite



Pro



Ultra



Part number	TC-C35VN Spec:13/E/Y/1.4mm/V4.2	TC-A32P6 Spec:E/4mm	TC-NC1261		
Max. Resolution	Up to 5MP,2592×1944@30fps	Up to 2MP,1920×1080@30fps	Up to 12MP,4000×3072@20fps		
Min. Illumination	Color:0.02Lux@(F2.0,AGC ON) B/W:0Lux with IR	Color: 0.002Lux@ (F1.6, AGC ON)	Color: 0.05Lux@ (F2.8, ACG ON) B/W: 0Lux with IR		
WDR	WDR	WDR	DWDR		
Lens	Fixed (1.4mm)	Fixed (4mm)	Fixed (1.98mm)		
Night Vision	IR range up to 30m	N/A	IR range up to 20m + Warmlight		
Body Material	Metal+plastic housing	Metal+plastic housing	Metal+plastic housing		
VCA	Tripwire; Double Tripwire; Perimeter; Heatmap	People Counting	Tripwire; Double Tripwire; Perimeter; Video Abnormal; Audio Abnormal; Heatmap		
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	Audio I/O: 1×input, 2×output Alarm I/O: 2×input, 1×output		
Protection	N/A	IP66	IP66, IK10		
Power Supply	DC12V±25%,Max. 8.5W PoE:IEEE 802.3af,Max. 9.5W	DC12V±25% PoE:IEEE 802.3af	DC12V±10%, AC24V±25% PoE:IEEE 802.3af		
Click Or Scan For More					
Price	485,000,000 ریال	Call	Call		



پرسیا سیستم



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

PTZ



Pro



Pro



Pro

Metal



Pro

Metal



Pro

Part number	TC-H324S Spec:23X//E/C/V3.0	TC-H324S Spec:23X//E/V3.0	TC-H324S Spec:25X//E/A/V/V3.0	TC-H326S Spec:33X//E+/A/V3.0	TC-H326S Spec:33X//E++/A
Max. Resolution	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@30fps	Up to 2MP,1920×1080@60fps
Lens	Motorized (5-115mm)	Motorized (5-115mm)	Motorized (4.8-120mm)	Motorized (4.6-152mm)	Motorized (4.6-152mm)
Optical Zoom	23X	23X	25X	33X	33X
Pan Range	360°	360°	360°	360°	360°
Vision	IR Up to 150m	IR Up to 150m	IR Up to 150m	IR Up to 200m	IR Up to 200m
Preset	500	500	500	500	500
VCA	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 4 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 5 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 11 more ...	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; + 9 more ...
Auto-Tracking	N/A	N/A	Yes	Yes	Yes
Audio I/O & Alarm I/O	N/A	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output	Audio I/O: 1×input, 1×output Alarm I/O: 8×input, 2×output
Protection	IP66	IP66	IP66	IP66	IP66
Click Or Scan For More					
Price	740,000,000 ریال	840,000,000 ریال	954,000,000 ریال	Call	Call



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

PTZ

	 Pro	 Metal	 Lite	 Pro	 Pro	 Metal	 Pro	 Metal	 Pro	 Pro
Part number	TC-H344S Spec:25X//E+/A/V3.0		TC-H354S Spec:23X//E/V3.0		TC-H354S Spec:23X//E/V3.1		TC-H356S Spec:30X//E++/A/V3.0		TC-H366V Spec:4MP/25X//W/E/A/2.8mm	
Max. Resolution	Up to 4MP,2560×1440@30fps		Up to 5MP,2880×1620@30fps		Up to 5MP,2880×1620@30fps		Up to 5MP,2880×1620@30fps		Panorama: 6MP,3840×1568@30fps Detail: 4MP,2560×1440@30fps	
Lens	Motorized (4.8-120mm)		Motorized (5-115mm)		Motorized (5-115mm)		Motorized (4.7-141mm)		Panorama: Fixed (2.8mm) Detail: Motorized (4.8-120mm)	
Optical Zoom	25X		23X		23X		30X		25X	
Pan Range	360°		360°		360°		360°		0~360°	
Vision	IR Up to 150m		IR Up to 150m		IR Up to 150m		IR Up to 200m		IR Up to 150m + Whitelight Up to 30m	
Preset	500		500		500		500		500	
VCA	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...		Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; + 10 more ...		Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...		Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...		Panorama: Tripwire; Double Tripwire; + 5 more ... Detail: Tripwire; + 15 more ...	
Auto-Tracking	Yes		N/A		N/A		Yes		Yes	
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output		Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output		Audio I/O: 1×input, 1×output Alarm I/O: 1×input, 1×output		Audio I/O: 1×input, 1×output Alarm I/O: 8×input, 2×output		Audio I/O: 1×input, 1×output Alarm I/O: 2×input, 1×output	
Protection	IP66		IP66		IP66		IP66		IP66	
Click Or Scan For More										
Price	ريال 1,190,000,000		ريال 1,330,000,000		ريال 1,330,000,000		Call		ريال 1,670,000,000	



 @Persiasystem
 info@ddcpersia.net

 02154871000
 DDCPERSIA.COM

به موارد فوق 10%
 ارزش افزوده اضافه میگردد



Tiandy

PTZ



Part number	TC-H348M Spec:63X/IL/E++/A	TC-H358M Spec:44X/IT/A	TC-H389M Spec:44X/LW/P/A		
Max. Resolution	Up to 4MP,2560×1440@30fps	Thermal: 384×288 Optical: 5MP,3072×1728@30fps	Panorama: 8MP,4096×1800@30fps Detail: 2MP,1920×1080@60fps		
Lens	Motorized (5.7-359mm)	Thermal: Fixed (50mm) Optical: Motorized (6-264mm)	Panorama: Fixed (5mm) Detail: Motorized (6-264mm)		
Optical Zoom	63X	44X	44X		
Pan Range	360°	360°	360°		
Vision	IR Up to 300m + Whitelight Up to 30m Laser Up to 500m	IR Up to 300m + Fire Detection Up to 3000m	Laser Up to 500m		
Preset	500	500	500		
VCA	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; + 12 more ...	Thermal: Tripwire; Double Tripwire; + 3 more ... Detail: Tripwire; + 13 more ...	Tripwire; Double Tripwire; Perimeter; Object Abandon; Object Missing; + 10 more ...		
Auto-Tracking	Yes	Yes	Yes		
Audio I/O & Alarm I/O	Audio I/O: 1×input, 1×output Alarm I/O: 8×input, 2×output	Audio I/O: 1×input, 1×output Alarm I/O: 8×input, 2×output	Audio I/O: 1×input, 1×output Alarm I/O: 8×input, 2×output		
Protection	IP66	IP66	IP66		
Click Or Scan For More					
Price	Call	Call	Call		



@ Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR

PoE



AK

PoE



AK



Spark



Spark

PoE



Spark

Part number	TC-R3104 Spec://B/P4/C/Eu/L/S	TC-R3108 Spec://B/P8/C/EU/L/S	TC-R3105 Spec://B/L/S/Eu	TC-R3105 Spec://B/L/S	TC-R3105 Spec://B/P/L/S
Access Channel	4	8	5	5	5
Incoming Bandwidth	60Mbps	60Mbps	60Mbps	60Mbps	60Mbps
Outgoing Bandwidth	40Mbps	40Mbps	40Mbps	40Mbps	40Mbps
Max. Resolution Support	5MP	6MP	6MP	5MP	6MP
Playback Decoding Capability	5MP×1, 4MP×1, 3MP×1, 1080P×2, 720P×4	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4	5MP×1, 4MP×1, 3MP×1, 1080P×2, 720P×4	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4
HDD Capacity	1×SATA, Up to 6 TB for each HDD	1×SATA, Up to 6 TB for each HDD	1×SATA, Up to 6 TB for each HDD	1×SATA, Up to 6 TB for each HDD	1×SATA, Up to 6 TB for each HDD
AI by NVR	N/A	N/A	N/A	N/A	N/A
Audio I/O & Alarm I/O	N/A	N/A	N/A	N/A	N/A
VCA Search	N/A	N/A	N/A	N/A	N/A
External Port	2×USB, 1×HDMI, 1×RJ-45	2×USB, 1×HDMI, 1×RJ-45	2×USB, 1×HDMI, 1×RJ-45	2×USB, 1×HDMI, 1×RJ-45	2×USB, 1×HDMI, 1×RJ-45
Click Or Scan For More					
Price	ريال 154,500,000	ريال 175,000,000	ريال 160,000,000	ريال 122,000,000	ريال 212,500,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR

PoE

PoE

Ai



Spark

Spark

Lite

Lite

Lite

TC-R3110
Spec: I/B/L/S/Eu

TC-R3110
Spec: I/B/P8/L/S

TC-R3105
Spec: I/B/L/Eu/V1.1

TC-R3105 44HA

TC-R3105
Spec: I/B/V3.0

Part number

Access Channel

Incoming Bandwidth

Outgoing Bandwidth

Max. Resolution Support

Playback Decoding Capability

HDD Capacity

AI by NVR

Audio I/O & Alarm I/O

VCA Search

External Port

Click Or Scan For More

Price

10

10

5

5

5

60Mbps

60Mbps

60Mbps

100Mbps

60Mbps

40Mbps

40Mbps

40Mbps

80Mbps

40Mbps

6MP

6MP

6MP

16MP

6MP

6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×3

6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4

6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4

16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×5, 1080P×5, 720P×5

6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4

1×SATA, Up to 6 TB for each HDD

1×SATA, Up to 6 TB for each HDD

1×SATA, Up to 8 TB for each HDD

1×SATA, Up to 10 TB for each HDD

1×SATA, Up to 10 TB for each HDD

N/A

N/A

N/A

Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection

N/A

N/A

N/A

N/A

Audio I/O: 1-ch × input, 1-ch × output
Alarm I/O: 4-ch × input, 1-ch × output

Audio Output: 1-ch × output

N/A

N/A

Early-warning Search

Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...

Early-warning Search

2×USB, 1×HDMI, 1×RJ-44

2×USB, 1×HDMI, 1×RJ-45

2×USB, 1×HDMI, 1×VGA, 1×RJ-45

2×USB, 1×HDMI, 1×VGA, 1×RJ-45

2×USB, 1×HDMI, 1×VGA, 1×RJ-45



ريال 190,000,000

ريال 246,000,000

ريال 166,200,000

ريال 527,500,000

ريال 287,700,000



@Persiasystem



info@ddcpersia.net



02154871000



DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR



Lite



Lite



Lite

AI



Lite



Lite

Part number	TC-R3110 Spec:I/B/L/Eu/V1.1	TC-R3110 Spec:I/B/L/V1.1	TC-R3110 4HA	TC-R3110 Spec:I/B/V3.0	TC-R3120 Spec:I/B/V3.0
Access Channel	10	10	10	10	20
Incoming Bandwidth	60Mbps	60Mbps	100Mbps	60Mbps	80Mbps
Outgoing Bandwidth	40Mbps	40Mbps	80Mbps	40Mbps	80Mbps
Max. Resolution Support	6MP	6MP	16MP	6MP	8MP
Playback Decoding Capability	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4	16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×6, 1080P×10, 720P×10	6MP×1, 5MP×1, 4MP×1, 3MP×2, 1080P×3, 720P×4	8MP×1, 6MP×1, 5MP×1, 4MP×2, 3MP×2, 1080P×4, 720P×8
HDD Capacity	1×SATA, Up to 8 TB for each HDD	1×SATA, Up to 8 TB for each HDD	1×SATA, Up to 10 TB for each HDD	1×SATA, Up to 10 TB for each HDD	1×SATA, Up to 10 TB for each HDD
AI by NVR	N/A	N/A	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection	N/A	N/A
Audio I/O & Alarm I/O	N/A	N/A	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio Output: 1-ch × output	Audio Output: 1-ch × output
VCA Search	Early-warning Search	Early-warning Search	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...	Early-warning Search	Early-warning Search; Behavior Search; Face Search
External Port	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45
Click Or Scan For More					
Price	ريال 201,400,000	Discontinue	ريال 360,000,000	ريال 293,500,000	ريال 300,000,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM


به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR

PoE

	  Lite 	  Lite 	  Lite 	  Lite 	  Lite
Part number	TC-R3120 4HA	TC-R3120 2MC	TC-R3210 4HA	TC-R3220 4HA	TC-R3220 Spec:I/B/P16/K/V3.0
Access Channel	20	20	10	20	20
Incoming Bandwidth	100Mbps	100Mbps	160Mbps (AI on: 120Mbps)	160Mbps (AI on: 120Mbps)	120Mbps
Outgoing Bandwidth	80Mbps	80Mbps	80Mbps	80Mbps	100Mbps
Max. Resolution Support	16MP	8MP	16MP	16MP	8MP
Playback Decoding Capability	16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×6, 1080P×10, 720P×16	8MP×2, 6MP×2, 5MP×3, 4MP×4, 3MP×5, 1080P×8, 720P×16	16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×6, 1080P×10, 720P×10	16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×6, 1080P×10, 720P×16	8MP×1, 6MP×1, 5MP×1, 4MP×2, 3MP×2, 1080P×4, 720P×8
HDD Capacity	1×SATA, Up to 10 TB for each HDD	1×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD
AI by NVR	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection	N/A	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection	N/A
Audio I/O & Alarm I/O	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio Input: 1-ch × input	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output
VCA Search	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 3 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...	N/A
External Port	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB2.0, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45
Click Or Scan For More					
Price	ريال 496,000,000	Call	ريال 550,000,000	ريال 605,000,000	ريال 630,000,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR

	 Lite	 Lite	 Lite	 Pro	 Pro
Part number	TC-R3232 Spec:I/B/K/V3.1	TC-R3232 4HA	TC-R3432 Spec:I/B/K/V3.1	TC-R3240 Spec:I/B/N/H/V4.0	TC-R3240 Spec:I/B/N/H/V4.1
Access Channel	32	32	32	40	40
Incoming Bandwidth	160Mbps	160Mbps (AI on: 120Mbps)	160Mbps	400Mbps	400Mbps
Outgoing Bandwidth	48Mbps	80Mbps	48Mbps	400Mbps	400Mbps
Max. Resolution Support	8MP	16MP	8MP	16MP	16MP
Playback Decoding Capability	8MP×2, 6MP×2, 5MP×3, 4MP×4, 3MP×5, 1080P×8, 720P×16	16MP×1, 8MP×2, 6MP×3, 5MP×4, 4MP×5, 3MP×6, 1080P×10, 720P×16	8MP×2, 6MP×2, 5MP×3, 4MP×4, 3MP×5, 1080P×8, 720P×16	16MP×2, 12MP×3, 8MP×4, 6MP×4, 5MP×6, 4MP×8, 3MP×9, 1080P×16, 720P×16	16MP×2, 12MP×3, 8MP×5, 6MP×6, 5MP×8, 4MP×10, 3MP×13, 1080P×20, 720P×40
HDD Capacity	2×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD	4×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD	2×SATA, Up to 10 TB for each HDD
AI by NVR	N/A	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; Smart Motion Detection	N/A	N/A	N/A
Audio I/O & Alarm I/O	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 4-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output
VCA Search	Heatmap; Early-warning Search; Behavior Search; Duty Search; + 3 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 4 more ...	Heatmap; Early-warning Search; Behavior Search; Duty Search; + 3 more ...	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Early-warning Search; Behavior Search; Duty Search; Thermographic Retrieval; + 2 more ...
External Port	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 1×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45
Click Or Scan For More					
Price	ريال 530,000,000	ريال 665,000,000	ريال 855,000,000	ريال 890,000,000	ريال 890,000,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد



Tiandy

NVR

	 Pro 	 Pro 	 Pro 	 Pro 	 Pro 
Part number	TC-R3240 4HB	TC-R3440 Spec:I/B/N/H/C/V4.0	TC-R3440 Spec:I/B/N/V4.0	TC-R3440 4MB	TC-R3440 4HB
Access Channel	40	40	40	40	40
Incoming Bandwidth	400Mbps (AI on: 200Mbps)	400Mbps	400Mbps	400Mbps (AI on: 200Mbps)	400Mbps (AI on: 200Mbps)
Outgoing Bandwidth	400Mbps (AI on: 200Mbps)	400Mbps	400Mbps	400Mbps (AI on: 200Mbps)	400Mbps (AI on: 200Mbps)
Max. Resolution Support	16MP	16MP	16MP	16MP	16MP
Playback Decoding Capability	16MP×3, 12MP×4, 8MP×7, 6MP×9, 5MP×11, 4MP×14, 3MP×16, 1080P×16, 720P×16	16MP×2, 12MP×3, 8MP×4, 6MP×4, 5MP×6, 4MP×8, 3MP×9, 1080P×16, 720P×16	16MP×2, 12MP×3, 8MP×4, 6MP×4, 5MP×6, 4MP×8, 3MP×9, 1080P×16, 720P×16	16MP×3, 12MP×4, 8MP×7, 6MP×9, 5MP×11, 4MP×14, 3MP×16, 1080P×16, 720P×16	16MP×3, 12MP×4, 8MP×7, 6MP×9, 5MP×11, 4MP×14, 3MP×16, 1080P×16, 720P×16
HDD Capacity	2×SATA, Up to 10 TB for each HDD	4×SATA, Up to 10 TB for each HDD	4×SATA, Up to 10 TB for each HDD	4×SATA, Up to 10 TB for each HDD	4×SATA, Up to 10 TB for each HDD
AI by NVR	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; + 10 more ...	N/A	N/A	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; + 10 more ...	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; + 10 more ...
Audio I/O & Alarm I/O	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output
VCA Search	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 7 more ...	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...
External Port	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45	2×USB, 1×HDMI, 1×VGA, 2×RJ-45
Click Or Scan For More					
Price	ريال 1,548,700,000	ريال 970,000,000	Call	ريال 1,715,800,000	ريال 2,140,000,000



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگرد



Tiandy

NVR

PoE



Pro



Pro



Pro



Pro

AI



Pro

Part number	TC-R3440 Spec:I/B/P16/H	TC-R3840 Spec:I/B/N/V4.0	TC-R3880 Spec:I/B/N/V4.0	TC-R3880 4HB	TC-R31680 Spec:E/B/N
Access Channel	40	40	80	80	80
Incoming Bandwidth	320Mbps	640Mbps	640Mbps	400Mbps (AI on: 320Mbps)	320Mbps
Outgoing Bandwidth	320Mbps	320Mbps	320Mbps	400Mbps (AI on: 200Mbps)	320Mbps
Max. Resolution Support	12MP	16MP	16MP	16MP	12MP
Playback Decoding Capability	12MP×3, 8MP×4, 6MP×4, 5MP×6, 4MP×8, 3MP×9, 1080P×16	16MP×3, 12MP×4, 8MP×6, 6MP×8, 5MP×9, 4MP×12, 3MP×16, 1080P×16, 720P×16	16MP×3, 12MP×4, 8MP×6, 6MP×8, 5MP×9, 4MP×12, 3MP×16, 1080P×16, 720P×16	16MP×3, 12MP×4, 8MP×7, 6MP×9, 5MP×11, 4MP×14, 3MP×16, 1080P×16, 720P×16	12MP×2, 8MP×4, 6MP×4, 5MP×5, 4MP×8, 3MP×9, 1080P×16, 720P×16
HDD Capacity	4×SATA, Up to 10 TB for each HDD	8×SATA, Up to 24 TB for each HDD	8×SATA, Up to 24 TB for each HDD	8×SATA, Up to 24 TB for each HDD	16×SATA, Up to 10 TB for each HDD
AI by NVR	N/A	N/A	N/A	Face Detection; Face Recognition; Tripwire; Double Tripwire; Perimeter; + 11 more ...	N/A
Audio I/O & Alarm I/O	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 1-ch × output Alarm I/O: 16-ch × input, 4-ch × output	Audio I/O: 1-ch × input, 2-ch × output Alarm I/O: 16-ch × input, 4-ch × output
VCA Search	N/A	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Heatmap; Early-warning Search; Behavior Search; Safety Helmet Search; + 5 more ...	Early-warning Search; Behavior Search; Safety Helmet Search; Duty Search; + 6 more ...	N/A
External Port	3×USB, 1×HDMI, 1×VGA, 1×RJ-45	1×eSATA, 3×USB, 2×HDMI, 2×VGA, 2×RJ-45	1×eSATA, 3×USB, 2×HDMI, 2×VGA, 2×RJ-45	1×eSATA, 3×USB, 2×HDMI, 2×VGA, 2×RJ-45	1×eSATA, 3×USB, 2×HDMI, 2×VGA, 2×RJ-45
Click Or Scan For More					
Price	Call	Call	2,576,400,000 ریال	Call	Call



@Persiasystem
info@ddcpersia.net

02154871000
DDCPERSIA.COM

به موارد فوق 10%
ارزش افزوده اضافه میگردد

